STEPLIGHT 1306

Recessed LED step light for interior and staircase installation, IP20



STEPLIGHT 1306 SERIES

The *Steplight 1306* is a recessed LED luminaire for interior and staircase lighting on board. A wide 100° beam provides even, glare-free illumination of steps, corridors and accommodation areas.

The light source is available in warm white, 2700 K or 3000 K, or as a combined red/white version (REWH) for night-vision-friendly operation. The luminaire combines an aluminium body with a polished stainless-steel front cover and flange, brushed finish optional, and a tool-free spring fixing for fast installation.

500 lm	2.5 W	27/30 K	REWH	100°	IP20
LIGHT OUTPUT	POWER	WARM WHITE	RED/WHITE OPT.	BEAM ANGLE	INGRESS

TECHNICAL SPECIFICATIONS

Product type	**LED steplight**	Supply voltage	**24 V DC**
Light source	**Warm white or red/white (REWH)**	Ingress protection	**IP20**
Power consumption	**2.5 W**	Material / finish	**Aluminium, polished stainless front**
Light output	**500 lm**	Dimensions	**90 × 90 × 55 mm**
Colour temperature	**2700 K or 3000 K**	Cutout	**77 × 70 mm**
Colour rendering (CRI)	**> 85**	Fixing	**2 springs, tool-free**
Beam angle	**100°**	Connection	**150 mm cable, Wieland connector**

FEATURES & CONSTRUCTION

Features

500 lm of even, glare-free light with a 100° beam and CRI over 85. Available in 2700 K or 3000 K warm white, or a combined red/white version (REWH) for night-vision-friendly operation. 24 V DC.

Construction

Aluminium body with a polished stainless-steel front cover and flange (90 × 90 mm), brushed finish optional. Tool-free spring fixing into a 77 × 70 mm cut-out. IP20, for dry interior, accommodation and staircase areas.

ORDERING INFORMATION

MODEL	FINISH	LIGHT	VOLTAGE	ORDER NO.
Steplight 1306	Polished stainless steel	2700 K or 3000 K warm white	24 V DC	**1306WH 24V**
Steplight 1306	Polished stainless steel	Red / white (REWH)	24 V DC	**1306REWH 24V**

Please specify colour temperature (2700 K or 3000 K) when ordering. Custom cable lengths and connectors on request.